




Soundbar 1 to 6.1 Solution



Title		
TELINK		
Size	Document Number	Rev
A4	C1T253A91_V1_1_20210909	1.1
Date:	Friday, September 10, 2021	Sheet 1 of 5




Module_A

Block diagram








Title		TELINK
Size A4	Document Number C1T253A91_V1_1_20210909	Rev V1.1
Date: Monday, November 22, 2021	Sheet 2 of 5	


Master



The resistor R1 is used to define the master-slave relationship.





The master provides a 24M clock for the slave.
The slave terminal receives about 1.2V,
and the IO voltage is 3.3V,
so it needs to be divided into 1/3.





Title		TELINK		
Size	Document Number			Rev
A3	C1T253A91_V1_1_20210909			V1.1
Date:	Monday October 18, 2021		Sheet	3 of 5

Slave_S1





Title	TELINK			
Size A4	Document Number C1T253A91_V1_1_20210909			Rev V1
Date:	Friday, September 10, 2021	Sheet	4	of 5

slave_S2



Title		TELINK	Rev
Size	Document Number	C1T253A91_V1_1_20210909	V1.1
Date:	Friday, September 10, 2021	Sheet	5 of 5

slave_S3



Title TELINK		
Size A4	Document Number C1T253A91_V1_1_20210909	Rev V1.1
Date: Friday, September 10, 2021	Sheet 5 of 5	